

BASELIFT 6300HA

Electric Height Adjustable Worktop Lift System – WALL Mounted - Straight Model



The Baselift 6300HA is an **electric height adjustable worktop lift system**, it is used to **lower** and **raise** worktops **vertically**. It is **wall** mounted and moves **up** and **down** at the touch of a button.

The Baselift 6300HA model has **increased** frame height for installation the of **sinks, cooktops, draws and chopping boards**. Equipment in the worktop surface is selected according to the desired function.

It can be used in **seated** or **standing** positions. The open area below/underneath the worktop surface provides extra space for legs and knees, thus allowing for easy and direct access.

A safety stop strip system is included and located below the front edge of the worktop. This stops the lift from lowering when it encounters objects or obstruction.

Baselift 6300HA offers accessories including: telescopic cover panels to conceal services below the worktop surface (motors, water, etc) creating a more discreet appearance.

The lifts can be used for **new** or **existing** installations and **relocated** (if required). They can be used separately or in conjunction with wall cabinet lifts to totally adapt the space.

Our height adjustable worktop lift systems help create **adaptable** and **functional** environments for individuals and facilities. This **assistive technology** caters for all ages, varying needs and abilities.



HOW - by making it easier, safer and more convenient to perform everyday tasks or activities, promoting participation and independence and helping to improve **accessibility** for all.

BASELIFT 6300HA

Electric Height Adjustable Worktop Lift System – WALL Mounted - Straight Model



Primary area of use is kitchens; however, the lift systems suit many other applications, including:

- Senior Living - individual homes, retirement facilities or aged care
- Disabilities - individual homes or supported/group homes
- Hospitals - rehabilitation facilities and other areas
- Workplace - reception, offices, canteen/meal room facilities, meeting areas
- Education - childcare, schools, Tafe, universities. (see our Education brochure)
- Other - retail and hospitality, leisure facilities

MODELS - BASELIFT 6300HA – WALL MOUNTED SYSTEMS - STRAIGHT



Baselift 6300HA

for widths 59cm to 100cm



Baselift 6300HA

for widths 109cm to 180cm



Baselift 6300HA

for widths 189cm to 240cm

Key Features:

- Adjustability - 30cm of continuous vertical height adjustment (70cm - 100cm) excl. worktop
- Sizes – custom worktop lifts from 59cm up to 240cm in width
- Operation – ALU control button is standard
- Safety – strip system is included
- Maximum Load – 100kg
- Frames supplied assembled – for quicker installation
- Manufacturer – Granberg of Sweden
- Warranty – 2 years manufacturers

Optional accessories:

- Fronts (aluminium), drawers, chopping board, locking systems to prevent misuse
- Cover panels - telescopic cover panels can be installed to hide the motor legs and provide a more discreet appearance for installation
- Cover panels dimensions – worktop width x height 43.8cm x thickness 1.2cm – 1.6cm
- Additional safety stop strips can be added for the sides of the lift
- Other control buttons - Mini Touch (code: 61318)

BASELIFT 6300HA

Electric Height Adjustable Worktop Lift System – WALL Mounted - Straight Model

Special note:

- The Baselift 6300HA straight model comes with an **increased** frame height
- The Baselift 6300HA straight model has superseded the Baselift 6200 straight model
- Product is customised and made-to-order and therefore non-returnable

Installation:

- Wall mounted and as per manufacturers manual
- Adjustment – 30cm
- Frame depth – 56.0 cm – 58.0cm from wall
- Worktop depth – 56.5cm – 63.0cm
- Front heights – 10.3cm
- Space - Lateral to wall/adjourning worktop or cabinet – 0.5cm
- Space – back wall to worktop 1.5cm (approx. for tiles)
- Plumbing – via flexible waste systems, plumber to supply and install
- Electric/Power – mains plug for 230/240v
- Delivered in modules – assembled worktop surface, including safety strip, wall mounted motors, ALU control button, fittings for fronts included

Technical:

- Height adjustment – motor driven, continuously adjustable
- Electrical connection – mains plug for 230/240V, max 2.5A
- Speed – 3.0cm/sec
- Maximum cycles – 6 per hour
- IP class – IP 20
- Frames – aluminium