

## BASELIFT 6300LA

Electric Height Adjustable Worktop Lift System – WALL Mounted - Straight Model



The **NEW** Baselift 6300LA is an **electric height adjustable worktop lift system**, used to **lower** and **raise** worktops **vertically**. It is **wall** mounted and moves **up** and **down** at the touch of a button.

The Baselift 6300LA model has a **shallow** frame height and allows for cooktop installation. It also can be used for many different applications including residential and commercial/office fitouts. Equipment in the worktop surface is selected according to the desired function.

It can be used in **seated** or **standing** positions. The open area below/underneath the worktop surface provides extra space for legs and knees, thus allowing for easy and direct access.

A safety stop strip system is included and located below the front edge of the worktop. This stops the lift from lowering when it encounters objects or obstruction.

Baselift 6300LA offers accessories including: telescopic cover panels to conceal services below the worktop surface (motors, water, etc) creating a more discreet appearance.

The lifts can be used for **new** or **existing** installations and **relocated** (if required). They can be used separately or in conjunction with wall cabinet lifts to totally adapt the space.

Our height adjustable worktop lift systems help create **adaptable** and **functional** environments for individuals and facilities. This **assistive technology** caters for all ages, varying needs and abilities.

**HOW** - by making it easier, safer and more convenient to perform everyday tasks or activities, promoting participation and independence and helping to improve **accessibility** for all.



## BASELIFT 6300LA

Electric Height Adjustable Worktop Lift System – WALL Mounted - Straight Model

Primary area of use are kitchens; however, the lift system suits many other applications, including:

- Senior Living - individual homes, retirement facilities or aged care
- Disabilities - individual homes or supported/group homes SDA's
- Hospitals - rehabilitation facilities and other areas
- Workplace - receptions, offices, canteen/meal room facilities, meeting areas
- Education - childcare, schools, Tafe, universities. (view our Education brochure)
- Other - retail and hospitality, leisure facilities.

### MODELS - BASELIFT 6300LA -SHALLOW FRAME HEIGHT- WALL MOUNTED SYSTEMS - STRAIGHT



Baselift 6300LA

for widths 59cm to 100cm



Baselift 6300LA

for widths 109cm to 180cm



Baselift 6300LA

for widths 189cm to 240cm

#### Key Features:

- Adjustability - 30cm of continuous vertical height adjustment (70cm - 100cm) excl. worktop
- Sizes – custom worktop lifts from 59cm upto 240cm in width
- Operation – Mini Touch (61318) control button is standard
- Safety – strip system is included
- Maximum Load – 100kg
- Frame supplied assembled – for quicker installation
- Manufacturer – Granberg of Sweden
- Warranty – 2 years manufacturers

#### Optional accessories:

- Fronts/fascia-aluminium, locking systems to prevent misuse
- Cover panels - telescopic cover panels can be installed to hide the motor legs and provide a more discreet appearance for installation
- Cover panels dimensions – worktop width x height 43.8cm x thickness 1.2cm – 1.6cm
- Additional safety stop strips can be added for the sides of the lift, required if the worktop is situated adjacent to other furniture

#### Special note:

- The Baselift 6300LA straight model comes with a **shallow** frame height.
- Baselift 6300LA has superseded the Slimlift 6250
- Product is customised and made-to-order and therefore non-returnable.

## BASELIFT 6300LA

Electric Height Adjustable Worktop Lift System – WALL Mounted - Straight Model

### Installation:

- Wall mounted and as per manufacturers manual
- Adjustment – 30cm
- Frame depth – 56.0 cm – 58.0cm from wall
- Worktop depth – 56.5cm – 63.0cm
- Front heights – 4.0cm
- Space - Lateral to wall/adjourning worktop or cabinet – 0.5cm
- Space – back wall to worktop 1.5cm (approx for tiles)
- Plumbing – via flexible waste systems, plumber to supply and install
- Electric/Power – mains plug for 230/240v
- Delivered in modules – worktop surface is supplied assembled- including safety strip, wall mounted motors, Mini touch control button, fittings for fronts included

### Technical:

- Height adjustment – motor driven, continuously adjustable
- Electrical connection – mains plug for 230/240V, max 2.5A
- Speed – 3.0cm/sec
- Maximum cycles – 6 per hour
- IP class – IP 20
- Frames – aluminium