

BASELIFT 6310HA

Electric Height Adjustable Worktop Lift System – FLOOR Mounted - CORNER Model



The Baselift 6310HA is an **electric height adjustable worktop lift system**, it is used to **lower** and **raise** worktops **vertically**. It is **floor** mounted and moves **up** and **down** at the touch of a button.

The Baselift 6310HA **FLOOR** mounted **CORNER** model is available in three different configurations to help meet a variety of situations. To compliment the corner units are the Plusmodule worktops, which are available in many sizes and can be fitted on either side of the corner units.

Why would you choose a **floor** mounted system? To enable installation when wall fixings are unavailable or difficult to achieve.

It can be used in **seated** or **standing** positions. The open area below/underneath the worktop surface provides extra space for legs and knees, thus allowing for easy and direct access.

A safety stop strip system is included and located below the front edge of the worktop. This stops the lift from lowering when it encounters objects or obstruction.

The Baselift 6300HA model has **increased** frame height for installation the of **sinks, cooktops, draws and chopping boards**. Equipment in the worktop surface is selected according to the desired function.

The lifts can be used for **new** or **existing** installations and **relocated** (if required). They can be used separately or in conjunction with wall cabinet lifts to totally adapt the space.

Baselift 6310HA **CORNER** models offers accessories including: telescopic cover panels to conceal services below the worktop surface (motors, water, etc) creating a more discreet appearance.

Our height adjustable worktop lift systems help create **adaptable** and **functional** environments for individuals and facilities. This **assistive technology** caters for all ages, varying needs and abilities.

HOW - by making it easier, safer and more convenient to perform everyday tasks or activities, promoting participation and independence and helping to improve **accessibility** for all.

BASELIFT 6310HA

Electric Height Adjustable Worktop Lift System – FLOOR Mounted - CORNER Model

Primary area of use is kitchens; however, the lift systems suit many other applications, including:

- Senior Living - individual homes, retirement facilities or aged care
- Disabilities - individual homes or supported/group homes
- Hospitals - rehabilitation facilities and other areas
- Workplace - reception, offices, canteen/meal room facilities, meeting areas
- Education - childcare, schools, Tafe, universities. (see our Education brochure)
- Other - retail and hospitality, leisure facilities

MODELS - BASELIFT 6310HA – FLOOR MOUNTED SYSTEMS - CORNER



CORNER 6311HA

90° wall, 45° front edge

104.5cm to 104.5cm



CORNER 6312HA

45° wall, 45° front edge

104.5cm to 104.5cm



CORNER 6313HA

90° wall, 90° front edge

59.5cm to 59.5cm

Key Features:

- Adjustability - 30cm of continuous vertical height adjustment (70cm - 100cm) excl. worktop
- Sizes – custom worktop lifts from 59cm up to 240cm in width
- Operation – ALU control button is standard
- Safety – strip system is included
- Maximum Load – 100kg
- Frames supplied assembled – for quicker installation
- Manufacturer – Granberg of Sweden
- Warranty – 2 years manufacturers



BASELIFT 6310HA

Electric Height Adjustable Worktop Lift System – FLOOR Mounted - CORNER Model

Optional accessories:

- For information on PLUSMODULE please contact Inclusive Living
- Fronts (aluminium), drawers, chopping board, locking systems to prevent misuse
- Cover panels - telescopic cover panels can be installed to hide the motor legs and provide a more discreet appearance for installation
- Cover panels dimensions – worktop width x height 43.8cm x thickness 1.2cm – 1.6cm
- Additional safety stop strips can be added for the sides of the lift

Special note:

- The Baselift 6310HA CORNER-**FLOOR** mounted comes with an **increased** frame height
- The Baselift 6310HA CORNER model has superseded the Baselift 6211, 6212, 6213 models
- Product is customised and made-to-order and therefore non-returnable

Installation:

- Wall mounted and as per manufacturers manual
- Adjustment – 30cm
- Frame depth – 56.0 cm – 58.0cm from wall
- Worktop depth – 56.5cm – 63.0cm
- Front heights – 10.3cm
- Space - Lateral to wall/adjourning worktop or cabinet – 0.5cm
- Space – back wall to worktop 1.5cm (approx. for tiles)
- Plumbing – via flexible waste systems, plumber to supply and install
- Electric/Power – mains plug for 230/240v
- Delivered in modules – assembled worktop surface, including safety strip, wall mounted motors, ALU control button, fittings for fronts included

Technical:

- Height adjustment – motor driven, continuously adjustable
- Electrical connection – mains plug for 230/240V, max 2.5A
- Speed – 3.0cm/sec
- Maximum cycles – 6 per hour
- IP class – IP 20
- Frames – aluminium