

BASELIFT 6310HA

Electric Height Adjustable Worktop Lift System – FLOOR Mounted - Straight Model

Baselift 6310HA - **STRAIGHT** model is a **FLOOR** mounted **electric height adjustable worktop lift system**. Used to **lower** and **raise** worktops **vertically**, at the touch of a button.

- Baselift STRAIGHT model is available in sizes ranging from 59.0cm up to 480.0cm widths
- **PLUSMODULES** can be added/fitted to either side allowing for greater accessibility
- **PLUSMODULES** sizes range from 40.0cm up to 240.0cm, available in left or right side
- Baselift 6310HA model have **increased** frame height for installation of **sinks, cooktops, drawers**. Equipment in the worktop surface is selected according to the desired function.
- Baselift models have a safety system underneath front edge and lowering stops when it encounters obstruction
- Baselift models offer a range of accessories including cover panels to conceal services below the worktop surface (motors, water, etc) creating a more discreet appearance



Why would you choose a **floor** mounted system? To enable installation when wall fixings are unavailable or difficult to achieve. Can also be used for freestanding kitchen island/peninsula.

Used in **seated** or **standing** positions, the open area below/underneath the worktop surface provides extra space for legs and knees, thus allowing for easy and direct access.

The lifts can be used for **new** or **existing** installations and **relocated** (if required). They can be used separately or in conjunction with wall cabinet lifts to totally adapt the space.

Our height adjustable worktop lift systems help create **adaptable** and **functional** environments for individuals and facilities. This **assistive technology** caters for all ages, varying needs and abilities.

HOW - by making it easier, safer and more convenient to perform everyday tasks or activities, promoting participation and independence and helping to improve **accessibility** for all.

BASELIFT 6310HA

Electric Height Adjustable Worktop Lift System – FLOOR Mounted - Straight Model

Primary area of use are kitchens; however, also suits many other applications, including:

- Senior Living - individual homes, retirement facilities or aged care
- Disabilities - individual homes or supported/group homes
- Hospitals - rehabilitation facilities and other areas
- Workplace - receptions, offices, canteen/meal room facilities, meeting areas
- **Education** - childcare, schools, Tafe, universities. (view our Education brochure)
- Other - retail and hospitality, leisure facilities.

MODELS - BASELIFT 6310HA - INCREASED FRAME HEIGHT- FLOOR MOUNTED SYSTEMS - STRAIGHT



Baselift 6310HA
for widths 59cm to 100cm



Baselift 6310HA
for widths 109cm to 180cm



Baselift 6310HA
for widths 189cm to 240cm



Baselift PLUSMODULE
40cm to 100cm



Baselift PLUSMODULE
110cm to 180cm



Baselift PLUSMODULE
190cm to 240cm

Plusmodules are also available in left side modules

Key Features:

- Size range of 59.0cm to 240.0cm widths and 480.0cm with **PLUSMODULE**.
- **PLUSMODULE** – 40.0cm up to 240.0cm contact Inclusive Living for further information
- Operation – ALU control button is standard
- Height Adjustment - 30cm
- Maximum Load – 100kg
- Safety – strip system is included
- Manufacturer – Granberg of Sweden
- Warranty – 2 years manufacturers
- Frame supplied assembled – for quicker installation

BASELIFT 6310HA

Electric Height Adjustable Worktop Lift System – FLOOR Mounted - Straight Model

Optional accessories:

- Fronts/fascia(aluminium), drawers, rear edge trim, locking systems to prevent misuse
- Cover panels - telescopic cover panels can be installed to hide the motor legs and provide a more discreet appearance for installation
- Cover panels dimensions – worktop width x height 43.8cm x thickness 1.2cm – 1.6cm
- Additional safety systems can be added for the sides of the lift, required if the worktop is situated adjacent to other furniture
- Mini touch control button

Special note:

- The Baselift 6310HA straight model comes with **increased** frame height
- Baselift 6310HA has superseded the Baselift 6210
- Product is customised and made-to-order and therefore non-returnable

Installation:

- FLOOR mounted and as per manufacturers manual
- Height Adjustment – 30cm
- Frame depth – 56.0 cm – 58.0cm from wall
- Worktop depth – 56.5cm – 63.0cm
- Worktop width/length range from 59.0cm up to 480.cm with **PLUSMODULE**
- Front heights – 10.3cm
- Space - Lateral to wall/adjourning worktop or cabinet – 0.5cm
- Space – back wall to worktop 1.5cm (approx for tiles)
- Plumbing – via flexible waste systems, plumber to supply and install
- Electric/Power – mains plug for 230/240v
- Delivered in modules – assembled worktop surface, including safety strip, wall mounted motors, ALU control button, fittings for fronts included

Technical:

- Height adjustment – motor driven, continuously adjustable
- Electrical connection – mains plug for 230/240V, max 2.5A
- Speed – 3.0cm/sec
- Maximum cycles – 6 per hour
- IP class – IP 20
- Frames – aluminium