

## BASELIFT 6310LA

Electric Height Adjustable Worktop Lift System – FLOOR Mounted - Straight Model

Baselift 6310LA - **STRAIGHT** model is a **FLOOR** mounted **electric height adjustable worktop lift system**. Used to **lower** and **raise** worktops **vertically**, at the touch of a button.

- Baselift STRAIGHT model is available in sizes ranging from 59.0cm up to 480.0cm widths
- **PLUSMODULES** can be added/fitted to either side allowing for greater accessibility
- **PLUSMODULES** sizes range from 40.0cm up to 240.0cm, available in left or right side
- Baselift 6310LA model have **shallow frame height** for installation of **cooktops**.
- Equipment in the worktop surface is selected according to the desired function.
- Baselift models have a safety system underneath front edge and lowering stops when it encounters obstruction
- Baselift models offer a range of accessories including cover panels to conceal services below the worktop surface (motors, water, etc) creating a more discreet appearance



Why would you choose a **floor** mounted system? To enable installation when wall fixings are unavailable or difficult to achieve.

Used in **seated** or **standing** positions, the open area below/underneath the worktop surface provides extra space for legs and knees, thus allowing for easy and direct access.

The lifts can be used for **new** or **existing** installations and **relocated** (if required). They can be used separately or in conjunction with wall cabinet lifts to totally adapt the space.

Our height adjustable worktop lift systems help create **adaptable** and **functional** environments for individuals and facilities. This **assistive technology** caters for all ages, varying needs and abilities.

**HOW** - by making it easier, safer and more convenient to perform everyday tasks or activities, promoting participation and independence and helping to improve **accessibility** for all.

# BASELIFT 6310LA

Electric Height Adjustable Worktop Lift System – FLOOR Mounted - Straight Model



**Primary area of use are kitchens;** also suits many other applications, including:

- Senior Living - individual homes, retirement facilities or aged care
- Disabilities - individual homes or supported/group homes
- Hospitals - rehabilitation facilities and other areas
- Workplace - receptions, offices, canteen/meal room facilities, meeting areas
- Education - childcare, schools, Tafe, universities. (view our Education brochure)
- Other - retail and hospitality, leisure facilities.

## MODELS - BASELIFT 6310LA -SHALLOW FRAME HEIGHT- FLOOR MOUNTED SYSTEMS - STRAIGHT



**Baselift 6310LA**  
for widths 59cm to 100cm



**Baselift 6310LA**  
for widths 109cm to 180cm



**Baselift 6310LA**  
for widths 189cm to 240cm



**Baselift PLUSMODULE**  
40cm to 100cm



**Baselift PLUSMODULE**  
110cm to 180cm



**Baselift PLUSMODULE**  
190cm to 240cm

Plusmodules are also available in left side modules

## BASELIFT 6310LA

Electric Height Adjustable Worktop Lift System – FLOOR Mounted - Straight Model

### Key Features:

- Size range of 59.0cm to 240.0cm widths and 480.0cm with **PLUSMODULE**
- **PLUSMODULE** – 40.0cm up to 240.0cm contact Inclusive Living for further information
- Operation – Mini Touch (61318) control button is standard
- Height Adjustment - 30cm
- Maximum Load – 100kg
- Safety – strip system is included
- Manufacturer – Granberg of Sweden
- Warranty – 2 years manufacturers
- Frame supplied assembled – for quicker installation

### Optional accessories:

- Fronts/fascia (aluminium), rear edge trim, locking systems to prevent misuse
- Cover panels - telescopic cover panels can be installed to hide the motor legs and provide a more discreet appearance for installation
- Cover panels dimensions – worktop width x height 43.8cm x thickness 1.2cm – 1.6cm
- Additional safety stop strips can be added for the sides of the lift, required if the worktop is situated adjacent to other furniture

### Special note:

- The Baselift 6310LA straight model comes with a **shallow** frame height
- Product is customised and made-to-order and therefore non-returnable

### Installation:

- FLOOR mounted and as per manufacturers manual
- Height Adjustment – 30cm
- Frame depth – 56.0 cm – 58.0cm from wall
- Worktop depth – 56.5cm – 63.0cm
- Size range of 59.0cm to 240.0cm widths and 480.0cm with **PLUSMODULE**
- Front heights – 4.0cm
- Space - Lateral to wall/adjourning worktop or cabinet – 0.5cm
- Space – back wall to worktop 1.5cm (approx. for tiles)
- Plumbing – via flexible waste systems, plumber to supply and install
- Electric/Power – mains plug for 230/240v
- Delivered in modules – assembled worktop surface, including safety strip, wall mounted motors, Mini touch control button, fittings for fronts included

### Technical:

- Height adjustment – motor driven, continuously adjustable
- Electrical connection – mains plug for 230/240V, max 2.5A
- Speed – 3.0cm/sec
- Maximum cycles – 6 per hour
- IP class – IP 20
- Frames – aluminium