

BASELIFT 6300HA

Electric Height Adjustable Worktop Lift System – WALL Mounted - CORNER Model



Baselift 6300HA – **CORNER** models – are **WALL** mounted **electric height adjustable worktop lift systems**. Used to **lower** and **raise** worktops **vertically**, at the touch of a button.

- Baselift CORNER models are available in **three** different configurations
- Models – 6301HA, 6302HA, 6303HA
- **PLUSMODULES** can be added/fitted to either side allowing for greater accessibility
- **PLUSMODULES** are available in many sizes and left and right side
- Baselift CORNER models have **increased** frame height for installation of **sinks, cooktops** and **drawers**
- Equipment in the worktop surface is selected according to the desired function
- Baselift models have a safety system underneath front edge and lowering stops when it encounters obstruction
- Baselift models offer a range of accessories including cover panels to conceal services below the worktop surface (motors, water, etc) creating a more discreet appearance

Used in **seated** or **standing** positions, the open area below/underneath the worktop surface provides extra space for legs and knees, thus allowing for easy and direct access.

The lifts can be used for **new** or **existing** installations and **relocated** (if required). They can be used separately or in conjunction with wall cabinet lifts to totally adapt the space.

Our height adjustable worktop lift systems help create **adaptable** and **functional** environments for individuals and facilities. This **assistive technology** caters for all ages, varying needs and abilities.

HOW - by making it easier, safer and more convenient to perform everyday tasks or activities, promoting participation and independence and helping to improve **accessibility** for all.

BASELIFT 6300HA**Electric Height Adjustable Worktop Lift System – WALL Mounted - CORNER Model**

Primary area of use is kitchens; also suits many other applications, including:

- Senior Living - individual homes, retirement facilities or aged care
- Disabilities - individual homes or supported/group homes
- Hospitals - rehabilitation facilities and other areas
- Workplace - reception, offices, canteen/meal room facilities, meeting areas
- Education - childcare, schools, Tafe, universities. (see our Education brochure)
- Other - retail and hospitality, leisure facilities

BASELIFT 6300HA

Electric Height Adjustable Worktop Lift System – WALL Mounted - CORNER Model

MODELS - BASELIFT 6300HA – WALL MOUNTED SYSTEMS - CORNER



CORNER 6301HA
90° wall, 45° front edge
104.5cm to 104.5cm



CORNER 6302HA
45° wall, 45° front edge
104.5cm to 104.5cm



CORNER 6303HA
90° wall, 90° front edge
59.5cm to 59.5cm



Baselift PLUSMODULE
40cm to 100cm



Baselift PLUSMODULE
110cm to 180cm



Baselift PLUSMODULE
190cm to 240cm

Plusmodules are also available in right side modules



BASELIFT 6300HA

Electric Height Adjustable Worktop Lift System – WALL Mounted - CORNER Model

Key Features:

- Sizes – depends upon model selected and **PLUSMODULE** size
- Operation – ALU control button is standard
- Height Adjustment - 30cm
- Maximum Load – 100kg
- Safety – strip system is included
- Manufacturer – Granberg of Sweden
- Warranty – 2 years manufacturers
- Frames supplied assembled – for quicker installation



Optional accessories:

- For information on **PLUSMODULE** please contact Inclusive Living
- Fronts (aluminium), drawers, chopping board, locking systems to prevent misuse
- Cover panels - telescopic cover panels can be installed to hide the motor legs and provide a more discreet appearance for installation
- Cover panels dimensions – worktop width x height 43.8cm x thickness 1.2cm – 1.6cm
- Additional safety stop strips can be added for the sides of the lift

Special note:

- The Baselift 6300HA CORNER-wall mounted series comes with an **increased** frame height
- The Baselift 6300HA CORNER model has superseded the Baselift 6201, 6202, 6203 models
- Product is customised and made-to-order and therefore non-returnable

Installation:

- Wall mounted and as per manufacturers manual
- Height Adjustment – 30cm
- Frame depth – 56.0 cm – 58.0cm from wall
- Worktop depth – 56.5cm – 63.0cm
- Front heights – 10.3cm
- Space - Lateral to wall/adjourning worktop or cabinet – 0.5cm
- Space – back wall to worktop 1.5cm (approx. for tiles)
- Plumbing – via flexible waste systems, plumber to supply and install
- Electric/Power – mains plug for 230/240v
- Delivered in modules – assembled worktop surface, including safety strip, wall mounted motors, ALU control button, fittings for fronts included

Technical:

- Height adjustment – motor driven, continuously adjustable
- Electrical connection – mains plug for 230/240V, max 2.5A
- Speed – 3.0cm/sec
- Maximum cycles – 6 per hour
- IP class – IP 20
- Frames – aluminium